

EVINRUDE® E-TEC® G2®

# 200 HP

## SPECIFICATIONS

<b>Engine Type</b>	V6 66° E-TEC G2 D.I.
<b>Bore x Stroke - in (mm)</b>	3.39 x 3.10 (86 x 78.7)
<b>Displacement - cu in (L)</b>	167 (2.7)
<b>Gear Ratio</b>	2.17:1
<b>Full Throttle RPM Range</b>	5000-6000 RPM
<b>Starting</b>	Electric
<b>Controls</b>	ICON II
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	133 Amps Total / 50 net Dedicated / 14 amps @ idle
<b>Trim Method</b>	Power Trim & Tilt
<b>Trim Range</b>	-6° to 15°
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - gal (L)</b>	On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
<b>Recommended Oil</b>	XPS Marine XD100
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	5-Year Engine** / 5-Year Corrosion
<b>Mounting Centers - in (mm)</b>	Minimum 26 (660)
<b>Color Customization</b>	Over 400 Color Panel Options
<b>Integrated Features</b>	Dual Axis Rigging / iTrim
<b>100% Global Emissions Compliant</b>	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)	TILT RANGE	STEERING ANGLE
Single	Slate Gray	20 (508)	iSteer DPS	C200GLF	530 (240)	81°	+/- 30°
			Remote	C200GLP	496 (225)	75°	+/- 32°
	Classic White	20 (508)	iSteer DPS	C200WLF	530 (240)	81°	+/- 30°
			Remote	C200WLP	496 (225)	75°	+/- 32°
Single <sup>†</sup> / Multiple	Slate Gray	25 (635)	iSteer DPS	C200GXF <sup>†</sup>	541 (245)	81°	+/- 30°
			IHS / Tiebar	C200GXC <sup>‡</sup>	533 (242)		
			Remote	C200GXP <sup>†</sup>	507 (230)	75°	+/- 32°
			Tiebar / Remote	C200GXCP <sup>‡</sup>	507 (230)		
	Classic White	25 (635)	iDOCK	C200GXA	541 (245)	81°	+/- 30°
			iDOCK	C200GXCA <sup>‡</sup>	533 (242)		
			iSteer DPS	C200WXF <sup>†</sup>	541 (245)	81°	+/- 30°
			IHS / Tiebar	C200WXC <sup>‡</sup>	533 (242)		
			Remote	C200WXP <sup>†</sup>	507 (230)	75°	+/- 32°
			Tiebar / Remote	C200WXCP <sup>‡</sup>	507 (230)		
iDOCK	C200WXA	541 (245)	81°	+/- 30°			
iDOCK	C200WXCA <sup>‡</sup>	533 (242)					

\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

† Standard Rotation iSteer DPS and Remote models available for single and multiple installation. All iDOCK models available for multiple installation only.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

**EVINRUDE®**