EVINRUDE[®] E-TEC[®] G2[®] **250 H.O.**

SPECIFICATIONS **Engine Type** H.O. V6 74° E-TEC G2 D.I. Bore x Stroke - in (mm) 3.85 x 3.00 (98 x 76) Displacement - cu in (L) 210 (3.4L) Gear Ratio 1.85:1 Full Throttle RPM Range 5400-6000 RPM Starting Electric Controls ICON II E-TEC Direct Injection with **Fuel Induction** stratified low RPM combustion mode 133 Amps Total / 50 net Dedicated / Alternator Output* 14 amps @ idle **Trim Method** Power Trim & Tilt -6° to 15° Trim Range Tilt Range 81° Multi-Point Targeted Oiling Lubrication On-Engine 2 (7.5) / Oil Tank Capacity - gal (L) Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85) Recommended Oil XPS Marine XD100 **Recommended Fuel** 87 Octane Warranty 5-Year Engine** / 5-Year Corrosion Mounting Centers - in (mm) Minimum 28 (711) **Color Customization** Over 400 Color Panel Options +/- 30° **Steering Angle Integrated Features** Dual Axis Rigging / iTrim 100% Global EPA 2013 / CARB 3 STAR / European Union **Emissions Compliant**



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - Ib (kg)
Single	Slate Gray	20 (508)	IHS	H250HGLO	537 (244)
			iSteer DPS	H250HGLF	547 (248)
	Classic White	20 (508)	iSteer DPS	H250HWLF	547 (248)
Single† / Multiple	Slate Gray	25 (635)	iSteer DPS IHS / Tiebar	H250HGXF [†] H250HGXC [‡]	558 (253) 558 (253)
			iDOCK iDOCK	H250HGXA H250GXCA [‡]	558 (253) 558 (253)
	Classic White	25 (635)	iSteer DPS IHS / Tiebar	H250HWXF [†] H250HWXC [‡]	558 (253) 558 (253)
			iDOCK iDOCK	H250HWXA H250WXCA‡	558 (253) 558 (253)

- ** 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.
- † Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK models available for multiple installation only.
- ‡ Corresponding Counter Rotation model.
- Specifications subject to change. ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

